

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**




FIG. 1: A NON-ISOLATED DOWN-CONVERTER USING SYNCHRONOUS RECTIFICATION AND AN ACTIVE DRIVE SCHEME.




FIG 2: AN ISOLATED FORWARD CONVERTER USING SYNCHRONOUS RECTIFICATION AND AN ACTIVE DRIVE SCHEME.




FIG 3: AN ISOLATED FORWARD CONVERTER USING SYNCHRONOUS RECTIFICATION A PASSIVE DRIVE SCHEME.




FIG 4: AN ISOLATED FORWARD CONVERTER WITH THE SYNCHRONOUS RECTIFIERS DRIVEN BY AUXILIARY TRANSFORMER WINDINGS.




FIG 5: ANOTHER ISOLATED DC/DC CONVERTER USING SYNCHRONOUS RECTIFIERS DRIVEN THROUGH PASSIVE CIRCUITRY.




FIG. 6: INSERTION OF A LOGIC GATE IN AN ACTIVE DRIVE CIRCUIT TO ENABLE/DISABLE A SYNCHRONOUS RECTIFIER.




FIG. 7: INSERTION OF A CONNECTION SWITCH AND A HOLD-OFF CIRCUITRY IN A PASSIVE GATE DRIVE CIRCUIT TO ENABLE/DISABLE A SYNCHRONOUS RECTIFIER.




FIG. 8: INSERTION OF A CONNECTION IMPEDANCE AND A HOLD-OFF CIRCUITRY IN A PASSIVE GATE DRIVE CIRCUIT TO ENABLE/DISABLE A SYNCHRONOUS RECTIFIER.




FIG. 9: A SPECIFIC IMPLEMENTATION OF THE CONCEPTS DEPICTED IN FIG. 8.




FIG. 10: THE IMPLEMENTATION OF FIG 9 MODIFIED SUCH THAT ONLY ONE TRANSISTOR IS USED IN THE HOLD-OFF CIRCUITRY FOR TWO SYNCHRONOUS RECTIFIERS.




FIG. 11 A NON-ISOLATED DOWN-CONVERTER USING SYNCHRONOUS RECTIFICATION AND A PASSIVE DRIVE.




FIG 12: AN ORING TRANSISTOR DRIVEN BY AN ACTIVE CONTROL CIRCUIT WITH A LOGIC GATE TO PROVIDE THE ENABLING/DISABLING FUNCTION.




FIG. 13: AN ORING TRANSISTOR DRIVEN BY WAVEFORMS IN THE POWER CIRCUIT SHOWN IN FIG. 5.






FIG. 14: DERIVING THE ENABLE/DISABLE SIGNAL FROM THE CONTROL CIRCUIT'S SHUTDOWN SIGNAL




FIG 15: A SPECIFIC IMPLEMENTATION OF THE CONCEPT DEPICTED IN FIG. 9 IN WHICH AN OPTO-ISOLATOR IS USED TO CONVEY THE ENABLE/DISABLE INPUT SIGNAL FROM THE INPUT SIDE CONTROL CIRCUIT.




FIG 16: USING A SWITCHING WAVEFORM IN THE POWER CIRCUIT TO INDICATE THAT THE CONVERTER HAS BEEN SHUTDOWN TO PROVIDE A "SHUTDOWN DECISION LOGIC SIGNAL".




FIG. 17: USING A COMPARATOR CIRCUIT TO DETECT THAT THE OUTPUT VOLTAGE IS TOO LOW AND TO DISABLE THE SYNCHRONOUS RECTIFIERS.




FIG 18: SENSING OUTPUT CURRENT DIRECTION INDIRECTLY THROUGH <sup>THE</sup> VOLTAGE DROP ACROSS THE SYNCHRONOUS RECTIFIERS.




FIG. 29: A DC/DC CONVERTER USING SYNCHRONOUS RECTIFIERS IN WHICH THE DECISION TO ENABLE/DISABLE THE RECTIFIERS IS PROVIDED BY AN EXTERNALLY ~~SEEN~~ SUPPLIED SIGNAL




FIG. 20: SLOWLY ENABLING A SYNCHRONOUS RECTIFIER  
BY GRADUALLY INCREASING  
ITS ON-STATE DURATION DURING ITS NORMAL  
CONDUCTION INTERVAL.




FIGURE 21: BLOCK DIAGRAM SHOWING DC/DC CONVERTER CONTROL CIRCUIT WITH A MINIMUM CURRENT LIMIT




FIG 22

09011383 070700

0001383 070700




FIGURE 23: ONE METHOD TO IMPLEMENT BOTH  
A MAXIMUM AND A MINIMUM CURRENT LIMIT.